



MODEL AP-24-PH



Specializing In Custom Heavy Equipment Trailers

Atoka Trailer & MFG. CO.
501 S. Jefferson HWY, Atoka, OK 74525
(580) 889-7270
www.atokatrailer.com

MODEL AP-24-PH

Standard Spec's

AT-24-PH TAG LIGHT UTILITY TRAILER:

11201 - STANDARD EQUIPMENT

8'-6" wide deck

5' tongue

Pintle eye (adjustable height (18 1/4" to 29 1/2"))

33 1/4' loaded deck height

(2) 12,000 lb. capacity axles 48 1/2" axle spacing

Dual 6 x 16 8-hole steel disc wheels

ST235/80R16 - 10 ply tires

12,000 lb. HD jack with spring foot

(10) D-rings

5' Ladder style ramps spring assist for ramps

Maximum adjustable ramps

Safety chains with grab hooks

Lockable tool box

Head board

I-beam cross members on 16" centers

Registration holder

LED lights

Rubber mounted sealed lights with sealed harness system

Electrical system per DOT regulations

Red and white conspicuity markings

Paint: Trail King 2-part polyurethane

1-1/2" Oak (raised) decking

Self-cleaning beavertail (includes mud flaps)

Ladder Style Ramps

Dexter Slipper Spring Suspensions

Air Brakes with 4S2M ABS

TK20/24LP CARC painted trailer (desert tan or olive green) color TK20/24LP

TK24LP Deck to be (25' flat w/5' beavertail) ILO 19' flat w/5' beavertail

12/24 volt lighting system