

A TOKA **T**RAILER & MFG

MODEL E1352



Specializing In Custom Heavy Equipment Trailers

Atoka Trailer & MFG. CO.
501 S. Jefferson HWY, Atoka, OK 74525
(580) 889-7270
www.atokatrailer.com

MODEL E1352

Standard Spec's

CAPACITY

- ◆70,000 # GVWR

GOOSENECK

- ◆10'10" LENGTH
- ◆84" SWING CLEARANCE
- ◆16" KINGPIN SEETTING
- ◆49" KINGPIN HEIGHT
- ◆1 PAIR D-RINGS

MAIN DECK

- ◆16" FABRICATED I-BEAM W/A514
- ◆FLANGES & A572 WEBBING
- ◆12" MILL CHANNEL SIDE RAIL
- ◆8" JR. I-BEAM CROSSMEMBERS ON 24"
- ◆CENTERS
- ◆1 ½" APITONG DECKING
- ◆4 D-RINGS PER SIDE
- ◆41" DECK HEIGHT W/COVERED WHEEL WELLS

OAL-OAW

- ◆APPROXIMATE 43' OAL
- ◆102" OAW

SUSPENSION

- ◆25K SPRING-HUTCH 9700

AXLES

- ◆(2) 22,500 LB NOMINAL
- ◆49 ¾" AXLE SPACING
- ◆77 ½" AXLE TRACK
- ◆HUB-PILOTED OUTBOARD DRUMS
- ◆16 ½" X 7" BRAKES AUTOMATIC SLACK
- ◆ADJUSTERS
- ◆4S2M ABS SYSTEM

WHEELS & TIRES

- ◆8.25" X 22.5" WHITE STEEL WHEELS
- ◆255/70R22.5 H-RATED TIRES

LIGHTING

- ◆DOT APPROVED 12V SEALED SYSTEM
- ◆RUBBER MOUNTED L.E.D. LIGHTS
- ◆1 MID-TURN PER SIDE 2 CLEARANCE PER SIDE
- ◆7-POLE ELECTRICAL SOCKET 2
- ◆TAIL-LIGHT PACKAGE
- ◆BEAVERTAIL & RAMPS
- ◆48" X 102" FULL-WIDTH
- ◆¼" SMOOTH PLATE W/ TRACTION AIDS
- ◆22" X 48" HD AIR-OPERATED RAMPS

LANDING GEAR

- ◆HOLLAND PIN-TYPE PARK STANDS

INSTALLED OPTIONS

- ◆22" X 60" AIR-OPERATED RAMPS
- ◆LOW DECK HEIGHT SPEC-37" DECK
- ◆HEIGHT W/ 4" RAISED COVERS
- ◆3/8" FORMED/RAISED COVERS W/ TRACTION AIDS
- ◆FULL-WIDTH GRADER RAMPS ON GOOSENECK
- ◆2 SPEED HOLLAND JACKS